



The world's leading supplier of broadband power amplifiers.

Model #: 7T500M-8C Frequency Range: 40-305 MHz

Specifications*



Operating frequency	40-305 MHz
Pulse power into 50 ohms per channel	500 W (min.)
CW power	N/A
Pulse width	20-100 msec typical.
Linearity (+/-1 dB, class AB)	500 W (min.)
Gain (0 dBm input)	+ 57 dB (nominal)
Gain flatness	+/- 3 dB, typ.
Harmonic content (2nd/3rd)	-20 dB/ -12 dBc, typ.
Input/ Output impedance	50 ohms (nominal)
Input VSWR	Less than 2:1
Duty cycle	10% (max.)
Amplitude rise/fall time	250 ns, typ.
Amplitude droop	5% to 20 ms. typ., 8% max.
Phase change / output power	12° to rated power, typ. 25° max.
Phase error overpulse	5° to 10 ms duration, typ.
Noise figure	12 dB typ.
Output noise (blanked)	20 dB over thermal, typ.
Blanking delay	1 μs, typ., on/off, TTL signal

Communication Power Corporation

80 Davids Drive, Suite 3
 Hauppauge, New York 11788
 Phone: 631. 434. 7306 Fax: 631. 434. 7026
 email: info@cpcamps.com
 Web Site: www.CPCAMPS.COM

* CPC reserves the right to change specifications without notice.



The world's leading supplier of broadband power amplifiers.

Model #: 7T500M-8C Frequency Range: 40-305 MHz



System Features



Protection functions:

- Auto/manual fault reset
- Maximum forward power
- Maximum average power
- Maximum VSWR
- Over temperature
- Power supply over voltage

Controls, front panel:

- AC power on/off
- Forward/ Reflected RF Power
- Fault reset
- Low power mode

Connectors, rear panel:

- AC mains, Receptacles, EMI filtered
- RF input: BNC (F) X8
- RF output: Type N (F) X8
- Noise blanking: BNC (F) dual polarity X8
- Interface: 25 pin D (F), EMI filtered
- Fwd/ Ref RF sample: SMA (F) X8
- Protective ground: threaded bolt

Front panel indicators:

- | | |
|--------------------|---------------------|
| AC power on | CW mode |
| Standby mode | Power supply status |
| RF overdrive fault | Thermal fault |
| VSWR fault | Blanking (Gate) |
| Energy fault | |

Interface functions:

- (C= Control Input F= Flag Output)
- CW mode (C/F) Standby (C/F)
- Power supply (F) RF overdrive (F)
- Thermal (F) VSWR (F)
- Energy (F)

Communication Power Corporation

80 Davids Drive, Suite 3
 Hauppauge, New York 11788
 Phone: 631. 434. 7306 Fax: 631. 434. 7026
 email: info@cpcamps.com
 Web Site: www.CPCAMPS.COM

* CPC reserves the right to change specifications without notice.